

## MANUAL DOWNRIGGER SPECIFICATIONS

MODEL	RETRIEVAL RATE (FPT)	WEIGHT CAPACITY (LB)	CLUTCH/BRAKE SYSTEM	SPOOL	BOOM	CABLE (FEET)	ROD HOLDER	SWIVEL BASE
MINI-TROLL	1	4	YES	Plastic	12" Lexan	100	NO	NO
LAKE-TROLL	1	8	YES	Plastic	18" Copolymer	100	YES (REAR)	NO
EASI-TROLL HS	1.5	8	YES	Plastic	24" Copolymer	150	YES (REAR)	NO
UNI-TROLL 5	1.5	20	YES	Plastic	24" Heavy-Duty	200	YES (REAR)	NO
UNI-TROLL 10	1.5	20	YES	Plastic	Heavy-Duty Telescopic*	200	YES (REAR)	YES
UNI-TROLL 10 TS	1.5	20	YES	Stainless Steel	S.S. Heavy-Duty Telescopic*	200	YES (REAR)	YES

FPT = FEET PER TURN \* EXTENDS 24" TO 53"

## ELECTRIC DOWNRIGGER SPECIFICATIONS

MODEL	RETRIEVAL RATE AT 12 LBS (FPM)	WEIGHT CAPACITY (LB)	SPOOL	BOOM	CABLE (FEET)	ROD HOLDER	SWIVEL BASE	SHORT STOP	POSITIVE ION CONTROL
MAG 5 ST	250	20	Plastic	S.S. 24" Heavy-Duty	250	Rear	NO	YES	YES
MAG 10 STX	250	20	Plastic	S.S. Heavy-Duty Telescopic*	250	Rear	YES	YES	YES
MAG 10 STX TS	250	20	Stainless Steel	S.S. Heavy-Duty Telescopic*	250	Rear	YES	YES	YES
DIGI-TROLL 5	250	20	Plastic	Heavy-Duty Telescopic*	400	Dual (REAR)	YES	YES	YES
DIGI-TROLL 5 TS	250	20	Stainless Steel	S.S. Heavy-Duty Telescopic*	400	Rear	YES	YES	YES
DIGI-TROLL 10	250	20	Plastic	Heavy-Duty Telescopic*	400	Dual (REAR)	YES	YES	YES (ADJ)
DIGI-TROLL 10 TS	250	20	Stainless Steel	S.S. Heavy-Duty Telescopic*	400	Rear	YES	YES	YES (ADJ)

FPM = FEET PER MINUTE \* EXTENDS 24" TO 53"