

MANUAL DOWNRIGGER SPECIFICATIONS

MODEL	RETRIEVE RATE (FPT)	WEIGHT CAPACITY (LB)	CLUTCH BRAKE SYSTEM	SPOOL	BOOM	CABLE (FEET)	ROD HOLDER	SWIVEL BASE
MINI-TROLL	1	4	YES	Plastic	12" Lexan	100	NO	NO
LAKE-TROLL	1	8	YES	Plastic	18" Copolymer	100	YES (REAR)	NO
EASI-TROLL HS	1.5	8	YES	Plastic	24" Copolymer	150	YES (REAR)	NO
UNI-TROLL 5	1.5	20	YES	Plastic	24" Heavy-Duty	200	YES (REAR)	NO
UNI-TROLL 10	1.5	20	YES	Plastic	Heavy-Duty Telescopic*	200	YES (REAR)	YES
UNI-TROLL 10TS	1.5	20	YES	Stainless Steel	S.S. Heavy-Duty Telescopic*	200	YES (REAR)	YES

FPT = FEET PER TURN * EXTENDS 24" TO 53"

ELECTRIC DOWNRIGGER SPECIFICATIONS

MODEL	RETRIEVE RATE AT 10 LBS (FPM)	WEIGHT CAPACITY (LB)	SPOOL	BOOM	CABLE (FEET)	ROD HOLDER	SWIVEL BASE	SHORT-STOP	POSITIVE ION CONTROL
MAG 5HS	250	20	Plastic	24" Heavy-Duty	250	Single (REAR)	NO	YES	YES
MAG 10HS	250	20	Plastic	Heavy-Duty Telescopic*	250	Single (REAR)	YES	YES	YES
MAG 20DT/HS	250	20	Plastic	Heavy-Duty Telescopic*	400	Dual (REAR)	YES	YES	YES (ADJ)
DIGI-TROLL IV HS	250	20	Plastic	Heavy-Duty Telescopic*	400	Dual (REAR)	YES	YES	YES (ADJ)
MAG 10TS	250	20	Stainless Steel	S.S. Heavy-Duty Telescopic*	400	Single (REAR)	YES	YES	YES
MAG 20DT/TS	250	20	Stainless Steel	S.S. Heavy-Duty Telescopic*	400	Single (REAR)	YES	YES	YES (ADJ)

FPM = FEET PER MINUTE * EXTENDS 24" TO 53"